



(12) UK Patent (19) GB (11) 2 398 319 (13) B

(45) Date of publication: 12.10.2005

(54) Title of the invention: Isolation of subterranean zones

(51) Int Cl<sup>7</sup>: E21B 43/14 43/02 43/10 43/12

(21) Application No: 0403894.9

(22) Date of Filing: 01.11.2002

Date Lodged: 20.02.2004

(30) Priority Data:  
(31) 10016467 (32) 10.12.2001 (33) US

(62) Divided from Application No  
0225505.7 under Section 15(4) of the Patents  
Act 1977

(43) Date A Publication: 18.08.2004

(52) UK CL (Edition X):  
E1F FAC FAC9 FJF FLA FLW

(56) Documents Cited:  
GB 2348223 A GB 2347446 A  
GB 2343691 A US 6263966 B  
US 3353599 A

(58) Field of Search:  
As for published application 2398319 A viz:  
UK CL (Edition W) E1F  
INT CL<sup>7</sup> E21B  
Other:  
updated as appropriate

(72) Inventor(s):  
Robert Lance Cook  
Lev Ring  
Kevin Waddell  
David Paul Brisco

(73) Proprietor(s):  
Shell Internationale Research  
Maatschappij B.V.  
(Incorporated in the Netherlands)  
Department IP/43 Carel Van Bylandtlaan  
30, 2596 HR The Hague, Netherlands

(74) Agent and/or Address for Service:  
Haseltine Lake & Co  
Redcliff Quay, 120 Redcliff Street,  
BRISTOL, BS1 6HU, United Kingdom

BEST AVAILABLE COPY

2358319

1/19




FIGURE 1

2/19




Fig. 2a




Fig. 2b

4/19




Fig. 2c




Fig. 2d




Fig. 3






Fig. 4



8/19



9/19

Fig. 5c




Fig. 5d




Fig. 5d

10/19

600




Fig. 6




Fig. 7

12/19




FIGURE 8




FIGURE 9

14/19





FIGURE 10








FIGURE 12

16/19





FIGURE 13





21 \* 3 05 2398319

## ISOLATION OF SUBTERRANEAN ZONES

### Background of the Invention

This invention relates generally to isolating certain subterranean zones.

During oil exploration, a wellbore typically traverses a number of zones within a subterranean formation. Some of these subterranean zones will produce oil and gas, while others will not. Further, it is often necessary to isolate subterranean zones from one another in order to facilitate the exploration for and production of oil and gas. Existing methods for isolating subterranean production zones in order to facilitate the exploration for and production of oil and gas are complex and expensive.

The present invention is directed to overcoming one or more of the limitations of the existing processes for isolating subterranean zones.

### Summary of the Invention

According to a first aspect of the present invention, there is provided an apparatus, comprising:

- a zonal isolation assembly positioned within a wellbore comprising:
  - one or more solid tubular members, each solid tubular member including one or more external seals;
  - one or more perforated tubular members each including radial passages coupled to the solid tubular members; and
  - one or more perforated tubular liners each including one or more radial passages coupled to the interior surfaces of one or more of the perforated tubular members; and
  - a shoe coupled to the zonal isolation assembly;
- wherein the perforated tubular members are formed by positioning the perforated tubular members within the wellbore and then radially expanding the perforated tubular members within the wellbore; and
- wherein the perforated tubular liners are formed by a radial expansion process performed within the wellbore.

According to another aspect of the present invention, there is provided a method of isolating a first subterranean zone from a second subterranean zone in a wellbore, comprising:

- positioning one or more solid tubulars within the wellbore, the solid tubulars traversing the first subterranean zone;

positioning one or more perforated tubulars each including one or more radial passages within the wellbore, the perforated tubulars traversing the second subterranean zone;

radially expanding the perforated tubulars within the wellbore;

5 fluidically coupling the perforated tubulars and the solid tubulars;

preventing the passage of fluids from the first subterranean zone to the second subterranean zone within the wellbore external to the solid tubulars and perforated tubulars;

10 positioning one or more perforated tubular liners within the interior of one or more of the perforated tubulars; and

radially expanding and plastically deforming the perforated tubular liners within the interior of one or more of the perforated tubulars.

According to another aspect of the present invention, there is provided a method of extracting materials from a producing subterranean zone in a wellbore, at least a  
15 portion of the wellbore including a casing, comprising;

positioning one or more solid tubulars within the wellbore;

positioning one or more perforated tubulars each including one or more radial passages within the wellbore, the perforated tubulars traversing the producing subterranean zone;

20 radially expanding the perforated tubulars within the wellbore;

fluidically coupling the solid tubulars with the casing;

fluidically coupling the perforated tubulars with the solid tubulars;


fluidically isolating the producing subterranean zone from at least one other subterranean zone within the wellbore;

25 fluidically coupling at least one of the perforated tubulars with the producing subterranean zone;

positioning one or more perforated tubular liners within the interior of one or more of the perforated tubulars; and

30 radially expanding and plastically deforming the perforated tubular liners within the interior of one or more of the perforated tubulars.

According to another aspect of the present invention, there is provided a system for isolating a first subterranean zone from a second subterranean zone in a wellbore, comprising:



means for positioning one or more solid tubulars within the wellbore, the solid tubulars traversing the first subterranean zone;

means for positioning one or more perforated tubulars each including one or more radial passages within the wellbore, the perforated tubulars traversing the second subterranean zone;

means for radially expanding the perforated tubulars within the wellbore;

means for fluidicly coupling the perforated tubulars and the solid tubulars;

means for preventing the passage of fluids from the first subterranean zone to the second subterranean zone within the wellbore external to the solid tubulars and perforated tubulars;

means for positioning one or more perforated tubular liners within the interior of one or more of the perforated tubulars; and

means for radially expanding and plastically deforming the perforated tubular liners within the interior of one or more of the perforated tubulars.

According to another aspect of the present invention, there is provided a system for extracting materials from a producing subterranean zone in a wellbore, at least a portion of the wellbore including a casing, comprising;

means for positioning one or more solid tubulars within the wellbore;

means for positioning one or more perforated tubulars each including one or more radial passages within the wellbore, the perforated tubulars traversing the producing subterranean zone;

means for radially expanding the perforated tubulars within the wellbore;

means for fluidicly coupling the solid tubulars with the casing;

means for fluidicly coupling the perforated tubulars with the solid tubulars;

means for fluidicly isolating the producing subterranean zone from at least one other subterranean zone within the wellbore;

means for fluidicly coupling at least one of the perforated tubulars with the producing subterranean zone;

means for positioning one or more perforated tubular liners within the interior of one or more of the perforated tubulars; and

means for radially expanding and plastically deforming the perforated tubular liners within the interior of one or more of the perforated tubulars.



According to another aspect of the present invention, there is provided apparatus for extracting geothermal energy from a subterranean formation containing a source of geothermal energy, comprising:

- 5 a zonal isolation assembly positioned within the subterranean formation, comprising:
  - one or more solid tubular members, each solid tubular member including one or more external seals;
  - one or more perforated tubular members each including radial passages coupled to the solid tubular members; and
  - 10 one or more perforated tubular liners each including one or more radial passages coupled to the interior surfaces of one or more of the perforated tubular members; and
  - a shoe coupled to the zonal isolation assembly;
  - wherein the perforated tubular members and the tubular liners are formed by a radial expansion process performed within a wellbore.

- 15 According to another aspect of the present invention, there is provided a method of isolating a first subterranean zone from a second subterranean zone including a source of geothermal energy in a wellbore, comprising:

- positioning one or more solid tubulars within the wellbore, the solid tubulars traversing the first subterranean zone;
- 20 positioning one or more perforated tubulars each including one or more radial passages within the wellbore, the perforated tubulars traversing the second subterranean zone;
- radially expanding the perforated tubulars within the wellbore;
- fluidically coupling the perforated tubulars and the solid tubulars;
- 25 preventing the passage of fluids from the first subterranean zone to the second subterranean zone within the wellbore external to the solid tubulars and perforated tubulars; and
- positioning one or more perforated tubular liners within the interior of one or more of the perforated tubulars; and
- 30 radially expanding and plastically deforming the perforated tubular liners within the interior of one or more of the perforated tubulars.

Preferably, a plurality of perforated tubular liners are coupled to the interior surfaces of one or more of the perforated tubular members.



Preferably, a plurality of perforated tubular liners are radially expanded into engagement with the interior surfaces of one or more of the perforated tubulars.

### Brief Description of the Drawings

5        FIG. 1 is a fragmentary cross-sectional view illustrating the isolation of subterranean zones.

      Fig. 2a is a cross sectional illustration of the placement of a system for isolating subterranean zones within a borehole.

10       Fig. 2b is a cross sectional illustration of the system of Fig. 2a during the injection of a fluidic material into the tubular support member.

      Fig. 2c is a cross sectional illustration of the system of Fig. 2b while pulling the tubular expansion cone out of the wellbore.

      Fig. 2d is a cross sectional illustration of the system of Fig. 2c after the tubular expansion cone has been completely pulled out of the wellbore.

15       Fig. 3 is a cross sectional illustration of the expandable tubular members of the system of Fig. 2a.

      Fig. 4 is a flow chart illustration of a method for manufacturing the expandable tubular member of Fig. 3.

20       Fig. 5a is a cross sectional illustration of the upsetting of the ends of a tubular member.

      Fig. 5b is a cross sectional illustration of the expandable tubular member of Fig. 5a after radially expanding and plastically deforming the ends of the expandable tubular member.

25       Fig. 5c is a cross sectional illustration of the expandable tubular member of Fig. 5b after forming threaded connections on the ends of the expandable tubular member.

      Fig. 5d is a cross sectional illustration of the expandable tubular member of Fig. 5c after coupling sealing members to the exterior surface of the intermediate unexpanded portion of the expandable tubular member.

30       Fig. 6 is a cross-sectional illustration of a tubular expansion cone.

      Fig. 7 is a cross-sectional illustration of a tubular expansion cone.

      Fig. 8 is a fragmentary cross sectional illustration of an alternative system for isolating subterranean zones of Fig. 1.



Fig. 9 is a fragmentary cross sectional illustration of a method for lining one of the perforated tubular members of the system for isolating subterranean zones of Fig. 1 with a solid tubular liner.

5 Fig. 10 is a fragmentary cross sectional illustration of a method for sealing one of the perforated tubular members of the system for isolating subterranean zones of Fig. 1 with a hardenable fluidic sealing material.

Fig. 11 is a fragmentary cross sectional illustration of a method for coupling one of the perforated tubular members of the system for isolating subterranean zones of Fig. 1 with the surrounding subterranean formation.

10 Fig. 12 is a fragmentary cross sectional illustration of a method for coupling one of the perforated tubular members of the system for isolating subterranean zones of Fig. 1 with a surrounding perforated wellbore casing.

Fig. 13 is a fragmentary cross sectional illustration of a method for lining one of the perforated tubular members of the system for isolating subterranean zones of Fig. 1 with another perforated tubular member.


15 Fig. 14 is a fragmentary cross sectional illustration of an alternative system for isolating subterranean zones of Fig. 1 that includes a one-way valve for preventing flow from a producing zone into a depleted zone.

20 Fig. 15 is a fragmentary cross sectional illustration of an alternative system for isolating subterranean zones of Fig. 1 in which the system is used to extract geothermal energy from a subterranean geothermal zone.

#### Detailed Description

An apparatus and method for isolating one or more subterranean zones from one or more other subterranean zones is provided. The apparatus and method permits a producing zone to be isolated from a nonproducing zone using a combination of solid and slotted tubulars. In the production mode, the teachings of the present disclosure may be used in combination with conventional, well known, production completion equipment and methods using a series of packers, solid tubing, perforated tubing, and sliding sleeves, which will be inserted into the disclosed apparatus to permit the commingling and/or isolation of the subterranean zones from each other.

Referring to Fig. 1, a wellbore 105 including a casing 110 are positioned in a subterranean formation 115. The subterranean formation 115 includes a number of productive and non-productive zones, including a water zone 120 and a targeted oil sand zone 125. During exploration of the subterranean formation 115, the wellbore



105 may be extended in a well known manner to traverse the various productive and non-productive zones, including the water zone 120 and the targeted oil sand zone 125.

5 In order to fluidically isolate the water zone 120 from the targeted oil sand zone 125, an apparatus 130 is provided that includes one or more sections of solid casing 135, one or more external seals 140, one or more sections of perforated casing 145, one or more intermediate sections of solid casing 150, and a solid shoe 155. The perforated casing 145 includes one or more radial passages.

10 The solid casing 135 provides a fluid conduit that transmits fluids and other materials from one end of the solid casing 135 to the other end of the solid casing 135. The solid casing 135 may comprise any number of conventional commercially available sections of solid tubular casing such as, for example, oilfield tubulars fabricated from chromium steel or fiberglass. The solid casing 135 comprises oilfield tubulars available from various foreign and domestic steel mills.

15 The solid casing 135 is preferably coupled to the casing 110. The solid casing 135 may be coupled to the casing 110 using any number of conventional commercially available processes such as, for example, welding, slotted and expandable connectors, or expandable solid connectors. The solid casing 135 is coupled to the casing 110 by using expandable solid connectors. The solid casing 135 may comprise a plurality of such solid casing 135.

20 The solid casing 135 is preferably coupled to one more of the perforated casings 145. The solid casing 135 may be coupled to the perforated casing 145 using any number of conventional commercially available processes such as, for example, welding, or slotted and expandable connectors. The solid casing 135 is coupled to the perforated casing 145 by expandable solid connectors.

25 The solid casing 135 includes one more valve members 160 for controlling the flow of fluids and other materials within the interior region of the casing 135. During the production mode of operation, an internal tubular string with various arrangements of packers, perforated tubing, sliding sleeves, and valves may be employed within the apparatus to provide various options for commingling and isolating subterranean zones from each other while providing a fluid path to the surface.

30 The casing 135 is placed into the wellbore 105 by expanding the casing 135 in the radial direction into intimate contact with the interior walls of the wellbore 105. The

casing 135 may be expanded in the radial direction using any number of conventional commercially available methods.

5 The seals 140 prevent the passage of fluids and other materials within the annular region 165 between the solid casings 135 and 150 and the wellbore 105. The seals 140 may comprise any number of conventional commercially available sealing materials suitable for sealing a casing in a wellbore such as, for example, lead, rubber or epoxy. The seals 140 comprise Stratalok epoxy material available from Halliburton Energy Services. The perforated casing 145 permits fluids and other materials to pass into and out of the interior of the perforated casing 145 from and to the annular region  
10 165. In this manner, oil and gas may be produced from a producing subterranean zone within a subterranean formation. The perforated casing 145 may comprise any number of conventional commercially available sections of slotted tubular casing. The perforated casing 145 comprises expandable slotted tubular casing available from Petrolite in Aberdeen, Scotland. The perforated casing 145 comprises expandable  
15 slotted sandscreen tubular casing available from Petrolite in Aberdeen, Scotland.

The perforated casing 145 is preferably coupled to one or more solid casing 135. The perforated casing 145 may be coupled to the solid casing 135 using any number of conventional commercially available processes such as, for example, welding, or slotted or solid expandable connectors. The perforated casing 145 is coupled to the  
20 solid casing 135 by expandable solid connectors.

The perforated casing 145 is preferably coupled to one or more intermediate solid casings 150. The perforated casing 145 may be coupled to the intermediate solid casing 150 using any number of conventional commercially available processes such as, for example, welding or expandable solid or slotted connectors. The perforated  
25 casing 145 is coupled to the intermediate solid casing 150 by expandable solid connectors.

The last perforated casing 145 is preferably coupled to the shoe 155. The last perforated casing 145 may be coupled to the shoe 155 using any number of conventional commercially available processes such as, for example, welding or expandable solid or slotted connectors. The last perforated casing 145 is coupled to  
30 the shoe 155 by an expandable solid connector.

Instead, the shoe 155 may be coupled directly to the last one of the intermediate solid casings 150.

The perforated casings 145 are positioned within the wellbore 105 by expanding the perforated casings 145 in a radial direction into intimate contact with the interior walls of the wellbore 105. The perforated casings 145 may be expanded in a radial direction using any number of conventional commercially available processes.

5 The intermediate solid casing 150 permits fluids and other materials to pass between adjacent perforated casings 145. The intermediate solid casing 150 may comprise any number of conventional commercially available sections of solid tubular casing such as, for example, oilfield tubulars fabricated from chromium steel or fiberglass. The intermediate solid casing 150 comprises oilfield tubulars available from  
10 foreign and domestic steel mills.

The intermediate solid casing 150 is preferably coupled to one or more sections of the perforated casing 145. The intermediate solid casing 150 may be coupled to the perforated casing 145 using any number of conventional commercially available processes such as, for example, welding, or solid or slotted expandable connectors.

15 The intermediate solid casing 150 is coupled to the perforated casing 145 by expandable solid connectors. The intermediate solid casing 150 may comprise a plurality of such intermediate solid casing 150.

Each intermediate solid casing 150 includes one more valve members 170 for controlling the flow of fluids and other materials within the interior region of the  
20 intermediate casing 150. As will be recognized by persons having ordinary skill in the art and the benefit of the present disclosure, during the production mode of operation, an internal tubular string with various arrangements of packers, perforated tubing, sliding sleeves, and valves may be employed within the apparatus to provide various options for commingling and isolating subterranean zones from each other while  
25 providing a fluid path to the surface.

The intermediate casing 150 is placed into the wellbore 105 by expanding the intermediate casing 150 in the radial direction into intimate contact with the interior walls of the wellbore 105. The intermediate casing 150 may be expanded in the radial direction using any number of conventional commercially available methods.

30 One or more of the intermediate solid casings 150 may be omitted. Preferably, one or more of the perforated casings 145 are provided with one or more seals 140.

The shoe 155 provides a support member for the apparatus 130. In this manner, various production and exploration tools may be supported by the shoe 150. The shoe 150 may comprise any number of conventional commercially available shoes suitable

for use in a wellbore such as, for example, cement filled shoe, or an aluminum or composite shoe. The shoe 150 comprises an aluminum shoe available from Halliburton. The shoe 155 is selected to provide sufficient strength in compression and tension to permit the use of high capacity production and exploration tools.

5       The apparatus 130 includes a plurality of solid casings 135, a plurality of seals 140, a plurality of perforated casings 145, a plurality of intermediate solid casings 150, and a shoe 155. More generally, the apparatus 130 may comprise one or more solid casings 135, each with one or more valve members 160, n perforated casings 145, n-1 intermediate solid casings 150, each with one or more valve members 170, and a shoe  
10   155.

During operation of the apparatus 130, oil and gas may be controllably produced from the targeted oil sand zone 125 using the perforated casings 145. The oil and gas may then be transported to a surface location using the solid casing 135. The use of intermediate solid casings 150 with valve members 170 permits isolated sections of the  
15   zone 125 to be selectively isolated for production. The seals 140 permit the zone 125 to be fluidically isolated from the zone 120. The seals 140 further permits isolated sections of the zone 125 to be fluidically isolated from each other. In this manner, the apparatus 130 permits unwanted and/or non-productive subterranean zones to be fluidically isolated.

20       As will be recognized by persons having ordinary skill in the art and also having the benefit of the present disclosure, during the production mode of operation, an internal tubular string with various arrangements of packers, perforated tubing, sliding sleeves, and valves may be employed within the apparatus to provide various options for commingling and isolating subterranean zones from each other while providing a  
25   fluid path to the surface.

The solid casing 135, the perforated casings 145, the intermediate sections of solid casing 150, and/or the solid shoe 155 may be radially expanded and plastically deformed within the wellbore 105 in a conventional manner and/or using one or more of the methods and apparatus disclosed in one or more of the following: (1) U.S. patent application serial no. 09/454,139, attorney docket no. 25791.03.02, filed on 12/3/1999,  
30   (2) U.S. patent application serial no. 09/510,913, attorney docket no. 25791.7.02, filed on 2/23/2000, (3) U.S. patent application serial no. 09/502,350, attorney docket no. 25791.8.02, filed on 2/10/2000, (4) U.S. patent application serial no. 09/440,338, attorney docket no. 25791.9.02, filed on 11/15/1999, (5) U.S. patent application serial


no. 09/523,460, attorney docket no. 25791.11.02, filed on 3/10/2000, (6) U.S. patent application serial no. 09/512,895, attorney docket no. 25791.12.02, filed on 2/24/2000, (7) U.S. patent application serial no. 09/511,941, attorney docket no. 25791.16.02, filed on 2/24/2000, (8) U.S. patent application serial no. 09/588,946, attorney docket no. 25791.17.02, filed on 6/7/2000, (9) U.S. patent application serial no. 09/559,122, attorney docket no. 25791.23.02, filed on 4/26/2000, (10) PCT patent application serial no. PCT/US00/18635, attorney docket no. 25791.25.02, filed on 7/9/2000, (11) U.S. provisional patent application serial no. 60/162,671, attorney docket no. 25791.27, filed on 11/1/1999, (12) U.S. provisional patent application serial no. 60/154,047, attorney docket no. 25791.29, filed on 9/16/1999, (13) U.S. provisional patent application serial no. 60/159,082, attorney docket no. 25791.34, filed on 10/12/1999, (14) U.S. provisional patent application serial no. 60/159,039, attorney docket no. 25791.36, filed on 10/12/1999, (15) U.S. provisional patent application serial no. 60/159,033, attorney docket no. 25791.37, filed on 10/12/1999, (16) U.S. provisional patent application serial no. 60/212,359, attorney docket no. 25791.38, filed on 6/19/2000, (17) U.S. provisional patent application serial no. 60/165,228, attorney docket no. 25791.39, filed on 11/12/1999, (18) U.S. provisional patent application serial no. 60/221,443, attorney docket no. 25791.45, filed on 7/28/2000, (19) U.S. provisional patent application serial no. 60/221,645, attorney docket no. 25791.46, filed on 7/28/2000, (20) U.S. provisional patent application serial no. 60/233,638, attorney docket no. 25791.47, filed on 9/18/2000, (21) U.S. provisional patent application serial no. 60/237,334, attorney docket no. 25791.48, filed on 10/2/2000, (22) U.S. provisional patent application serial no. 60/270,007, attorney docket no. 25791.50, filed on 2/20/2001; (23) U.S. provisional patent application serial no. 60/262,434, attorney docket no. 25791.51, filed on 1/17/2001; (24) U.S. provisional patent application serial no. 60/259,486, attorney docket no. 25791.52, filed on 1/3/2001; (25) U.S. provisional patent application serial no. 60/303,740, attorney docket no. 25791.61, filed on 7/6/2001; (26) U.S. provisional patent application serial no. 60/313,453, attorney docket no. 25791.59, filed on 8/20/2001; (27) U.S. provisional patent application serial no. 60/317,985, attorney docket no. 25791.67, filed on 9/6/2001; (28) U.S. provisional patent application serial no. 60/318,386, attorney docket no. 25791.67.02, filed on 9/10/2001; and (29) U.S. utility patent application serial no. 09/969,922, attorney docket no. 25791.69, filed on 10/3/2001. The radial clearances between the radially expanded solid casings 135, perforated casings 145, intermediate sections of solid casing 150, and/or the solid shoe

155 and the wellbore 105 may be eliminated thereby eliminating the annulus between the solid casings, the perforated casings 145, the intermediate sections of solid casing 150, and/or the solid shoe 155 and the wellbore 105. In this manner, the optional need for filling the annulus with a filler material such as, for example, gravel, may be eliminated.

Referring to Figs. 2a-2d, a system 200 for isolating subterranean formations includes a tubular support member 202 that defines a passage 202a. A tubular expansion cone 204 that defines a passage 204a is coupled to an end of the tubular support member 202. The tubular expansion cone 204 includes a tapered outer surface 204b for reasons to be described.

A pre-expanded end 206a of a first expandable tubular member 206 that defines a passage 206b is adapted to mate with and be supported by the tapered outer surface 204b of the tubular expansion cone 204. The first expandable tubular member 206 further includes an unexpanded intermediate portion 206c, another pre-expanded end 206d, and a sealing member 206e coupled to the exterior surface of the unexpanded intermediate portion. The inside and outside diameters of the pre-expanded ends, 206a and 206d, of the first expandable tubular member 206 are greater than the inside and outside diameters of the unexpanded intermediate portion 206c. An end 208a of a shoe 208 is coupled to the pre-expanded end 206a of the first expandable tubular member 206 by a conventional threaded connection.

An end 210a of a slotted tubular member 210 that defines a passage 210b is coupled to the other pre-expanded end 206d of the first expandable tubular member 206 by a conventional threaded connection. Another end 210c of the slotted tubular member 210 is coupled to an end 212a of a slotted tubular member 212 that defines a passage 212b by a conventional threaded connection. A pre-expanded end 214a of a second expandable tubular member 214 that defines a passage 214b is coupled to the other end 212c of the tubular member 212. The second expandable tubular member 214 further includes an unexpanded intermediate portion 214c, another pre-expanded end 214d, and a sealing member 214e coupled to the exterior surface of the unexpanded intermediate portion. The inside and outside diameters of the pre-expanded ends, 214a and 214d, of the second expandable tubular member 214 are greater than the inside and outside diameters of the unexpanded intermediate portion 214c.





An end 216a of a slotted tubular member 216 that defines a passage 216b is coupled to the other pre-expanded end 214d of the second expandable tubular member 214 by a conventional threaded connection. Another end 216c of the slotted tubular member 216 is coupled to an end 218a of a slotted tubular member 218 that defines a passage 218b by a conventional threaded connection. A pre-expanded end 220a of a third expandable tubular member 220 that defines a passage 220b is coupled to the other end 218c of the slotted tubular member 218. The third expandable tubular member 220 further includes an unexpanded intermediate portion 220c, another pre-expanded end 220d, and a sealing member 220e coupled to the exterior surface of the unexpanded intermediate portion. The inside and outside diameters of the pre-expanded ends, 220a and 220d, of the third expandable tubular member 220 are greater than the inside and outside diameters of the unexpanded intermediate portion 220c.

An end 222a of a tubular member 222 is threadably coupled to the end 30d of the third expandable tubular member 220.

The inside and outside diameters of the pre-expanded ends, 206a, 206d, 214a, 214d, 220a and 220d, of the expandable tubular members, 206, 214, and 220, and the slotted tubular members 210, 212, 216, and 218, may be substantially equal. The sealing members, 206e, 214e, and 220e, of the expandable tubular members, 206, 214, and 220, respectively, further include anchoring elements for engaging the wellbore casing 104. The slotted tubular members, 210, 212, 216, and 218, may be conventional slotted tubular members having threaded end connections suitable for use in an oil or gas well, an underground pipeline, or as a structural support. The slotted tubular members, 210, 212, 216, and 218 may be conventional slotted tubular members for recovering or introducing fluidic materials such as, for example, oil, gas and/or water from or into a subterranean formation.

As illustrated in Fig. 2a, the system 200 is initially positioned in a borehole 224 formed in a subterranean formation 226 that includes a water zone 226a and a targeted oil sand zone 226b. The borehole 224 may be positioned in any orientation from vertical to horizontal. The upper end of the tubular support member 202 may be supported in a conventional manner using, for example, a slip joint, or equivalent device in order to permit upward movement of the tubular support member and tubular expansion cone 204 relative to one or more of the expandable tubular members, 206, 214, and 220, and tubular members, 210, 212, 216, and 218.



As illustrated in Fig. 2b, a fluidic material 228 is then injected into the system 200, through the passages, 202a and 204a, of the tubular support member 202 and tubular expansion cone 204, respectively.

As illustrated in Fig. 2c, the continued injection of the fluidic material 228 through  
5 the passages, 202a and 204a, of the tubular support member 202 and the tubular expansion cone 204, respectively, pressurizes the passage 18b of the shoe 18 below the tubular expansion cone thereby radially expanding and plastically deforming the expandable tubular member 206 off of the tapered external surface 204b of the tubular expansion cone 204. In particular, the intermediate non pre-expanded portion 206c of  
10 the expandable tubular member 206 is radially expanded and plastically deformed off of the tapered external surface 204b of the tubular expansion cone 204. As a result, the sealing member 206e engages the interior surface of the wellbore casing 104. Consequently, the radially expanded intermediate portion 206c of the expandable tubular member 206 is thereby coupled to the wellbore casing 104. The radially  
15 expanded intermediate portion 206c of the expandable tubular member 206 is also thereby anchored to the wellbore casing 104.

As illustrated in Fig. 2d, after the expandable tubular member 206 has been plastically deformed and radially expanded off of the tapered external surface 204b of the tubular expansion cone 204, the tubular expansion cone is pulled out of the  
20 borehole 224 by applying an upward force to the tubular support member 202. As a result, the second and third expandable tubular members, 214 and 220, are radially expanded and plastically deformed off of the tapered external surface 204b of the tubular expansion cone 204. In particular, the intermediate non pre-expanded portion 214c of the second expandable tubular member 214 is radially expanded and  
25 plastically deformed off of the tapered external surface 204b of the tubular expansion cone 204. As a result, the sealing member 214e engages the interior surface of the wellbore 224. Consequently, the radially expanded intermediate portion 214c of the second expandable tubular member 214 is thereby coupled to the wellbore 224. The radially expanded intermediate portion 214c of the second expandable tubular member  
30 214 is also thereby anchored to the wellbore 104. Furthermore, the continued application of the upward force to the tubular member 202 will then displace the tubular expansion cone 204 upwardly into engagement with the pre-expanded end 220a of the third expandable tubular member 220. Finally, the continued application of the upward force to the tubular member 202 will then radially expand and plastically



deform the third expandable tubular member 220 off of the tapered external surface 204b of the tubular expansion cone 204. In particular, the intermediate non pre-expanded portion 220c of the third expandable tubular member 220 is radially expanded and plastically deformed off of the tapered external surface 204b of the tubular expansion cone 204. As a result, the sealing member 220e engages the interior surface of the wellbore 224. Consequently, the radially expanded intermediate portion 220c of the third expandable tubular member 220 is thereby coupled to the wellbore 224. The radially expanded intermediate portion 220c of the third expandable tubular member 220 is also thereby anchored to the wellbore 224. As a result, the water zone 226a and fluidly isolated from the targeted oil sand zone 226b.


After completing the radial expansion and plastic deformation of the third expandable tubular member 220, the tubular support member 202 and the tubular expansion cone 204 are removed from the wellbore 224.

Thus, during the operation of the system 10, the intermediate non pre-expanded portions, 206c, 214c, and 220c, of the expandable tubular members, 206, 214, and 220, respectively, are radially expanded and plastically deformed by the upward displacement of the tubular expansion cone 204. As a result, the sealing members, 206e, 214e, and 220e, are displaced in the radial direction into engagement with the wellbore 224 thereby coupling the shoe 208, the expandable tubular member 206, the slotted tubular members, 210 and 212, the expandable tubular member 214, the slotted tubular members, 216 and 218, and the expandable tubular member 220 to the wellbore. Furthermore, as a result, the connections between the expandable tubular members, 206, 214, and 220, the shoe 208, and the slotted tubular members, 210, 212, 216, and 218, do not have to be expandable connections thereby providing significant cost savings. In addition, the inside diameters of the expandable tubular members, 206, 214, and 220, and the slotted tubular members, 210, 212, 216, and 218, after the radial expansion process, are substantially equal. In this manner, additional conventional tools and other conventional equipment may be easily positioned within, and moved through, the expandable and slotted tubular members. The conventional tools and equipment include conventional valving and other conventional flow control devices for controlling the flow of fluidic materials within and between the expandable tubular members, 206, 214, and 220, and the slotted tubular members, 210, 212, 216, and 218.

Furthermore, in the system 200, the slotted tubular members 210, 212, 216, and 218 are interleaved among the expandable tubular members, 206, 214, and 220. As a result, because only the intermediate non pre-expanded portions, 206c, 214c, and 220c, of the expandable tubular members, 206, 214, and 220, respectively, are radially expanded and plastically deformed, the slotted tubular members, 210, 212, 216, and 218 can be conventional slotted tubular members thereby significantly reducing the cost and complexity of the system 10. Moreover, because only the intermediate non pre-expanded portions, 206c, 214c, and 220c, of the expandable tubular members, 206, 214, and 220, respectively, are radially expanded and plastically deformed, the number and length of the interleaved slotted tubular members, 210, 212, 216, and 218 can be much greater than the number and length of the expandable tubular members. The total length of the intermediate non pre-expanded portions, 206c, 214c, and 220c, of the expandable tubular members, 206, 214, and 220, is approximately 61 m (200 feet), and the total length of the slotted tubular members, 210, 212, 216, and 218, is approximately 1158 m (3800 feet). Consequently, A system 200 having a total length of approximately 1219 m (4000 feet) is coupled to the wellbore 224 by radially expanding and plastically deforming a total length of only approximately 61 m (200 feet).

Furthermore, the sealing members 206e, 214e, and 220e, of the expandable tubular members, 206, 214, and 220, respectively, are used to couple the expandable tubular members and the slotted tubular members, 210, 212, 216, and 218 to the wellbore 224, the radial gap between the slotted tubular members, the expandable tubular members, and the wellbore 224 may be large enough to effectively eliminate the possibility of damage to the expandable tubular members and slotted tubular members during the placement of the system 200 within the wellbore.

The pre-expanded ends, 206a, 206d, 214a, 214d, 220a, and 220d, of the expandable tubular members, 206, 214, and 220, respectively, and the slotted tubular members, 210, 212, 216, and 218, have outside diameters and wall thicknesses of 213 mm (8.375 inches) and 8.89 mm (0.350 inches), respectively; prior to the radial expansion, the intermediate non pre-expanded portions, 206c, 214c, and 220c, of the expandable tubular members, 206, 214, and 220, respectively, have outside diameters of 194 mm (7.625 inches); the slotted tubular members, 210, 212, 216, and 218, have inside diameters of 195 mm (7.675 inches); after the radial expansion, the inside diameters of the intermediate portions, 206c, 214c, and 220c, of the expandable



tubular members, 206, 214, and 220, are equal to 195 mm (7.675 inches); and the wellbore 224 has an inside diameter of 222 mm (8.755 inches).

The pre-expanded ends, 206a, 206d, 214a, 214d, 220a, and 220d, of the expandable tubular members, 206, 214, and 220, respectively, and the slotted tubular members, 210, 212, 216, and 218, have outside diameters and wall thicknesses of 114 mm (4.500 inches) and 6.35 mm (0.250 inches), respectively; prior to the radial expansion, the intermediate non pre-expanded portions, 206c, 214c, and 220c, of the expandable tubular members, 206, 214, and 220, respectively, have outside diameters of 102 mm (4.000 inches); the slotted tubular members, 210, 212, 216, and 218, have inside diameters of 102 mm (4.000 inches); after the radial expansion, the inside diameters of the intermediate portions, 206c, 214c, and 220c, of the expandable tubular members, 206, 214, and 220, are equal to 102 mm (4.000 inches); and the wellbore 224 has an inside diameter of 124 mm (4.892 inches).


The system 200 is used to inject or extract fluidic materials such as, for example, oil, gas, and/or water into or from the subterranean formation 226b.

Referring now to Fig. 3, another expandable tubular member 300 will now be described. The tubular member 300 defines an interior region 300a and includes a first end 300b including a first threaded connection 300ba, a first tapered portion 300c, an intermediate portion 300d, a second tapered portion 300e, and a second end 300f including a second threaded connection 300fa. The tubular member 300 further preferably includes an intermediate sealing member 300g that is coupled to the exterior surface of the intermediate portion 300d.

The tubular member 300 has a substantially annular cross section. The tubular member 300 may be fabricated from any number of conventional commercially available materials such as, for example, Oilfield Country Tubular Goods (OCTG), 13 chromium steel tubing/casing, or L83, J55, or P110 API casing.

The interior 300a of the tubular member 300 has a substantially circular cross section. Furthermore, The interior region 300a of the tubular member includes a first inside diameter  $D_1$ , an intermediate inside diameter  $D_{INT}$ , and a second inside diameter  $D_2$ . The first and second inside diameters,  $D_1$  and  $D_2$ , are substantially equal. The first and second inside diameters,  $D_1$  and  $D_2$ , are greater than the intermediate inside diameter  $D_{INT}$ .

The first end 300b of the tubular member 300 is coupled to the intermediate portion 300d by the first tapered portion 300c, and the second end 300f of the tubular



member is coupled to the intermediate portion by the second tapered portion 300e. The outside diameters of the first and second ends, 300b and 300f, of the tubular member 300 is greater than the outside diameter of the intermediate portion 300d of the tubular member. The first and second ends, 300b and 300f, of the tubular member  
 5 300 include wall thicknesses,  $t_1$  and  $t_2$ , respectively. The outside diameter of the intermediate portion 300d of the tubular member 300 ranges from about 75% to 98% of the outside diameters of the first and second ends, 300a and 300f. The intermediate portion 300d of the tubular member 300 includes a wall thickness  $t_{INT}$ .

The wall thicknesses  $t_1$  and  $t_2$  are substantially equal in order to provide  
 10 substantially equal burst strength for the first and second ends, 300a and 300f, of the tubular member 300. The wall thicknesses,  $t_1$  and  $t_2$ , are both greater than the wall thickness  $t_{INT}$  in order to optimally match the burst strength of the first and second ends, 300a and 300f, of the tubular member 300 with the intermediate portion 300d of the tubular member 300.

The first and second tapered portions, 300c and 300e, may be inclined at an  
 15 angle,  $\alpha$ , relative to the longitudinal direction ranging from about 0 to 30 degrees in order to optimally facilitate the radial expansion of the tubular member 300. The first and second tapered portions, 300c and 300e, provide a smooth transition between the first and second ends, 300a and 300f, and the intermediate portion 300d, of the tubular  
 20 member 300 in order to minimize stress concentrations.

The intermediate sealing member 300g is coupled to the outer surface of the intermediate portion 300d of the tubular member 300. The intermediate sealing member 300g seals the interface between the intermediate portion 300d of the tubular member 300 and the interior surface of a wellbore casing 305, or other preexisting  
 25 structure, after the radial expansion and plastic deformation of the intermediate portion 300d of the tubular member 300. The intermediate sealing member 300g has a substantially annular cross section. The outside diameter of the intermediate sealing member 300g is selected to be less than the outside diameters of the first and second ends, 300a and 300f, of the tubular member 300 in order to optimally protect the  
 30 intermediate sealing member 300g during placement of the tubular member 300 within the wellbore casings 305. The intermediate sealing member 300g may be fabricated from any number of conventional commercially available materials such as, for example, thermoset or thermoplastic polymers. The intermediate sealing member 300g is fabricated from thermoset polymers in order to optimally seal the radially



expanded intermediate portion 300d of the tubular member 300 with the wellbore casing 305. The sealing member 300g may include one or more rigid anchors for engaging the wellbore casing 305 to thereby anchor the radially expanded and plastically deformed intermediate portion 300d of the tubular member 300 to the wellbore casing.

Referring to Figs. 4, and 5a to 5d, The tubular member 300 is formed by a process 400 that includes the steps of: (1) upsetting both ends of a tubular member in step 405; (2) expanding both upset ends of the tubular member in step 410; (3) stress relieving both expanded upset ends of the tubular member in step 415; (4) forming threaded connections in both expanded upset ends of the tubular member in step 420; and (5) putting a sealing material on the outside diameter of the non-expanded intermediate portion of the tubular member in step 425.

As illustrated in FIG. 5a, in step 405, both ends, 500a and 500b, of a tubular member 500 are upset using conventional upsetting methods. The upset ends, 500a and 500b, of the tubular member 500 include the wall thicknesses  $t_1$  and  $t_2$ . The intermediate portion 500c of the tubular member 500 includes the wall thickness  $t_{INT}$  and the interior diameter  $D_{INT}$ . The wall thicknesses  $t_1$  and  $t_2$  are substantially equal in order to provide burst strength that is substantially equal along the entire length of the tubular member 500. The wall thicknesses  $t_1$  and  $t_2$  are both greater than the wall thickness  $t_{INT}$  in order to provide burst strength that is substantially equal along the entire length of the tubular member 500, and also to optimally facilitate the formation of threaded connections in the first and second ends, 500a and 500b.

As illustrated in Fig. 5b, in steps 410 and 415, both ends, 500a and 500b, of the tubular member 500 are radially expanded using conventional radial expansion methods, and then both ends, 500a and 500b, of the tubular member are stress relieved. The radially expanded ends, 500a and 500b, of the tubular member 500 include the interior diameters  $D_1$  and  $D_2$ . The interior diameters  $D_1$  and  $D_2$  are substantially equal in order to provide a burst strength that is substantially equal. The ratio of the interior diameters  $D_1$  and  $D_2$  to the interior diameter  $D_{INT}$  ranges from about 100% to 120% in order to facilitate the subsequent radial expansion of the tubular member 500.

The relationship between the wall thicknesses  $t_1$ ,  $t_2$ , and  $t_{INT}$  of the tubular member 500; the inside diameters  $D_1$ ,  $D_2$  and  $D_{INT}$  of the tubular member 500; the inside diameter  $D_{wellbore}$  of the wellbore casing, or other structure, that the tubular

member 500 will be inserted into; and the outside diameter  $D_{cone}$  of the expansion cone that will be used to radially expand the tubular member 500 within the wellbore casing is given by the following expression:

$$D_{wellbore} - 2 * t_1 \geq \frac{1}{t_1} [(t_1 - t_{INT}) * D_{cone} + t_{INT} * D_{INT}]$$

5 where  $t_1 = t_2$ ; and

$$D_1 = D_2.$$

By satisfying the relationship given in equation (1), the expansion forces placed upon the tubular member 500 during the subsequent radial expansion process are substantially equalized. More generally, the relationship given in equation (1) may be  
10 used to calculate the optimal geometry for the tubular member 500 for subsequent radial expansion and plastic deformation of the tubular member 500 for fabricating and/or repairing a wellbore casing, a pipeline, or a structural support.

As illustrated in FIG. 5c, in step 420, conventional threaded connections, 500d and 500e, are formed in both expanded ends, 500a and 500b, of the tubular member  
15 500. The threaded connections, 500d and 500e, are provided using conventional processes for forming pin and box type threaded connections available from Atlas-Bradford.

As illustrated in Fig. 5d, in step 425, a sealing member 500f is then applied onto the outside diameter of the non-expanded intermediate portion 500c of the tubular  
20 member 500. The sealing member 500f may be applied to the outside diameter of the non-expanded intermediate portion 500c of the tubular member 500 using any number of conventional commercially available methods. The sealing member 500f is applied to the outside diameter of the intermediate portion 500c of the tubular member 500 using commercially available chemical and temperature resistant adhesive bonding.

25 The expandable tubular members, 206, 214, and 220, of the system 200 may be substantially identical to, and/or incorporate one or more of the teachings of, the tubular members 300 and 500.


Referring to Fig. 6, a tubular expansion cone 600 for radially expanding the tubular members 206, 214, 220, 300 and 500 will now be described. The expansion  
30 cone 600 defines a passage 600a and includes a front end 605, a rear end 610, and a radial expansion section 615.

The radial expansion section 615 includes a first conical outer surface 620 and a second conical outer surface 625. The first conical outer surface 620 includes an angle



of attack  $\alpha_1$  and the second conical outer surface 625 includes an angle of attack  $\alpha_2$ . The angle of attack  $\alpha_1$  is greater than the angle of attack  $\alpha_2$ . In this manner, the first conical outer surface 620 optimally radially expands the intermediate portions, 206c, 214c, 220c, 300d, and 500c, of the tubular members, 206, 214, 220, 300, and 500, and the second conical outer surface 525 optimally radially expands the pre-expanded first and second ends, 206a and 206d, 214a and 214d, 220a and 220d, 300b and 300f, and 500a and 500b, of the tubular members, 206, 214, 220, 300 and 500. The first conical outer surface 620 includes an angle of attack  $\alpha_1$  ranging from about 8 to 20 degrees, and the second conical outer surface 625 includes an angle of attack  $\alpha_2$  ranging from about 4 to 15 degrees in order to optimally radially expand and plastically deform the tubular members, 206, 214, 220, 300 and 500. More generally, the expansion cone 600 may include 3 or more adjacent conical outer surfaces having angles of attack that decrease from the front end 605 of the expansion cone 600 to the rear end 610 of the expansion cone 600.

Referring to Fig. 7, another tubular expansion cone 700 defines a passage 700a and includes a front end 705, a rear end 710, and a radial expansion section 715. The radial expansion section 715 includes an outer surface having a substantially parabolic outer profile thereby providing a paraboloid shape. In this manner, the outer surface of the radial expansion section 715 provides an angle of attack that constantly decreases from a maximum at the front end 705 of the expansion cone 700 to a minimum at the rear end 710 of the expansion cone. The parabolic outer profile of the outer surface of the radial expansion section 715 may be formed using a plurality of adjacent discrete conical sections and/or using a continuous curved surface. In this manner, the region of the outer surface of the radial expansion section 715 adjacent to the front end 705 of the expansion cone 700 may optimally radially expand the intermediate portions, 206c, 214c, 220c, 300d, and 500c, of the tubular members, 206, 214, 220, 300, and 500, while the region of the outer surface of the radial expansion section 715 adjacent to the rear end 710 of the expansion cone 700 may optimally radially expand the pre-expanded first and second ends, 206a and 206d, 214a and 214d, 220a and 220d, 300b and 300f, and 500a and 500b, of the tubular members, 206, 214, 220, 300 and 500. The parabolic profile of the outer surface of the radial expansion section 715 is selected to provide an angle of attack that ranges from about 8 to 20 degrees in the vicinity of the front end 705 of the expansion cone 700 and an angle of attack in the vicinity of the rear end 710 of the expansion cone 700 from about 4 to 15 degrees.



The tubular expansion cone 204 of the system 200 is substantially identical to the expansion cones 600 or 700, and/or incorporates one or more of the teachings of the expansion cones 600 and/or 700.

5 The teachings of the apparatus 130, the system 200, the expandable tubular member 300, the method 400, and/or the expandable tubular member 500 may be at least partially combined.

Referring to Fig. 8, conventional temperature, pressure, and flow sensors, 802, 804, and 806, respectively, are operably coupled to the perforated tubulars 145 of the apparatus 130. The temperature, pressure, and flow sensors, 802, 804, and 806, 10 respectively, in turn are operably coupled to a controller 810 that receives and processes the output signals generated by the temperature, pressure, and flow sensors to thereby control the operation of the flow control valves 160 to enhance the operational efficiency of the apparatus 130. The control algorithms utilized by the controller 810 for controlling the operation of the flow control valves 160 as a function 15 of the operating temperature, pressure, and flow rates within the perforated tubular members 145 are conventional.

Referring to Fig. 9, a solid tubular member 905 is coupled to one of the perforated tubular members 145 by radially expanding and plastically deforming the solid tubular member into engagement with the perforated tubular member in a 20 conventional manner and/or using one or more of the radial expansion methods disclosed in one or more of the following: (1) U.S. patent application serial no. 09/454,139, attorney docket no. 25791.03.02, filed on 12/3/1999, (2) U.S. patent application serial no. 09/510,913, attorney docket no. 25791.7.02, filed on 2/23/2000, (3) U.S. patent application serial no. 09/502,350, attorney docket no. 25791.8.02, filed 25 on 2/10/2000, (4) U.S. patent application serial no. 09/440,338, attorney docket no. 25791.9.02, filed on 11/15/1999, (5) U.S. patent application serial no. 09/523,460, attorney docket no. 25791.11.02, filed on 3/10/2000, (6) U.S. patent application serial no. 09/512,895, attorney docket no. 25791.12.02, filed on 2/24/2000, (7) U.S. patent application serial no. 09/511,941, attorney docket no. 25791.16.02, filed on 2/24/2000, 30 (8) U.S. patent application serial no. 09/588,946, attorney docket no. 25791.17.02, filed on 6/7/2000, (9) U.S. patent application serial no. 09/559,122, attorney docket no. 25791.23.02, filed on 4/26/2000, (10) PCT patent application serial no. PCT/US00/18635, attorney docket no. 25791.25.02, filed on 7/9/2000, (11) U.S. provisional patent application serial no. 60/162,671, attorney docket no. 25791.27, filed

on 11/1/1999, (12) U.S. provisional patent application serial no. 60/154,047, attorney docket no. 25791.29, filed on 9/16/1999, (13) U.S. provisional patent application serial no. 60/159,082, attorney docket no. 25791.34, filed on 10/12/1999, (14) U.S. provisional patent application serial no. 60/159,039, attorney docket no. 25791.36, filed  
5 on 10/12/1999, (15) U.S. provisional patent application serial no. 60/159,033, attorney docket no. 25791.37, filed on 10/12/1999, (16) U.S. provisional patent application serial no. 60/212,359, attorney docket no. 25791.38, filed on 6/19/2000, (17) U.S. provisional patent application serial no. 60/165,228, attorney docket no. 25791.39, filed on 11/12/1999, (18) U.S. provisional patent application serial no. 60/221,443, attorney  
10 docket no. 25791.45, filed on 7/28/2000, (19) U.S. provisional patent application serial no. 60/221,645, attorney docket no. 25791.46, filed on 7/28/2000, (20) U.S. provisional patent application serial no. 60/233,638, attorney docket no. 25791.47, filed on 9/18/2000, (21) U.S. provisional patent application serial no. 60/237,334, attorney docket no. 25791.48, filed on 10/2/2000, (22) U.S. provisional patent application serial  
15 no. 60/270,007, attorney docket no. 25791.50, filed on 2/20/2001; (23) U.S. provisional patent application serial no. 60/262,434, attorney docket no. 25791.51, filed on 1/17/2001; (24) U.S. provisional patent application serial no. 60/259,486, attorney docket no. 25791.52, filed on 1/3/2001; (25) U.S. provisional patent application serial no. 60/303,740, attorney docket no. 25791.61, filed on 7/6/2001; (26) U.S. provisional  
20 patent application serial no. 60/313,453, attorney docket no. 25791.59, filed on 8/20/2001; (27) U.S. provisional patent application serial no. 60/317,985, attorney docket no. 25791.67, filed on 9/6/2001; (28) U.S. provisional patent application serial no. 60,318,386, attorney docket no. 25791.67.02, filed on 9/10/2001; and (29) U.S. utility patent application serial no. 09/969,922, attorney docket no. 25791.69, filed on  
25 10/3/2001. In this manner, the solid tubular member 905 fluidically seals the radial passages formed in the perforated tubular member 145 thereby preventing the passage of fluidic materials and/or formation materials through the perforated tubular member.

Referring to Fig. 10, the radial openings in one of the perforated tubular members  
30 145 are sealed by injecting a hardenable fluidic sealing material 1005 into the radial openings in the one perforated tubular member by positioning a closed ended pipe 1010 having one or more radial openings 1010a within the one perforated tubular member 145. Conventional sealing members 1015 and 1020 then seal the interface between the pipe 1010 and the opposite ends of the one perforated tubular member


145. The hardenable fluidic sealing material 1005 is then injected into the radial openings in the one perforated tubular member 145. The sealing members 140 prevent the passage of the hardenable fluidic sealing material out of the annulus between the one perforated tubular member 145 and the formation 125. The pipe 1010 and sealing members, 1015 and 1020, are then removed from the apparatus 130, and the hardenable fluidic sealing material is allowed to cure. A conventional drill string may then be used to remove any excess cured sealing material from the interior surface of the one perforated tubular member 145. The hardenable fluidic sealing material is a curable epoxy resin.

10 As illustrated in Fig. 11, one or more of the perforated tubular members 145 of the apparatus 130 may be radially expanded and plastically deformed into contact with the surrounding formation 125 thereby compressing the surrounding formation. In this manner, the surrounding formation 125 is maintained in a state of compression thereby stabilizing the surrounding formation, reducing the flow of loose particles from the  
15 surrounding formation into the radial openings of the perforated tubular member 145, and enhancing the recovery of hydrocarbons from the surrounding formation.

A seismic source 1105 is positioned on a surface location to thereby impart seismic energy into the formation 125. In this manner, particles lodged in the radial openings in the perforated tubular member 145 may be dislodged from the radial  
20 openings thereby enhancing the subsequent recovery of hydrocarbons from the formation 125.

After the perforated tubular member 145 has been radially expanded and plastically formed into contact with the surrounding formation 125, thereby coupling the perforated tubular member 145 to the surrounding formation, an impulsive load is  
25 applied to the perforated tubular member. The impulsive load may be applied to the perforated tubular member 145 by applying the load to the end of the apparatus 130. The impulsive load is then transferred to the surrounding formation 125 thereby compacting and/or slurrifying the surrounding formation. As a result, the recovery of hydrocarbons from the formation 125 is enhanced.

30 As illustrated in Fig. 12, a wellbore casing 1205 having one or more perforations 1210 may be positioned within the wellbore 105 that traverses the formation 125. When the apparatus 130 is positioned within the wellbore 105, one or more of the perforated tubular members 145 of the apparatus 130 are radially expanded and plastically deformed into contact with the wellbore casing 1205 thereby compressing



the surrounding formation 125. In this manner, the surrounding formation 125 is maintained in a state of compression thereby stabilizing the surrounding formation, reducing the flow of loose particles from the surrounding formation into the radial openings of the perforated tubular member 145, and enhancing the recovery of hydrocarbons from the surrounding formation.

A seismic source 1215 is positioned on a surface location to thereby impart seismic energy into the formation 125. In this manner, particles lodged in the radial openings in the perforated tubular member 145 may be dislodged from the radial openings thereby enhancing the subsequent recovery of hydrocarbons from the formation 125.

After the perforated tubular member 145 has been radially expanded and plastically formed into contact with the wellbore casing 1205, thereby coupling the perforated tubular member 145 to the surrounding formation, an impulsive load is applied to the perforated tubular member. The impulsive load may be applied to the perforated tubular member 145 by applying the load to the end of the apparatus 130. The impulsive load is then transferred to the surrounding formation 125 thereby compacting and/or slurrifying the surrounding formation. As a result, the recovery of hydrocarbons from the formation 125 is enhanced.

Referring to Fig. 13, one or more perforated tubular members 1305 are coupled to one of the perforated tubular members 145 by radially expanding and plastically deforming the perforated tubular member into engagement with the perforated tubular member in a conventional manner and/or using one or more of the radial expansion methods disclosed in one or more of the following: (1) U.S. patent application serial no. 09/454,139, attorney docket no. 25791.03.02, filed on 12/3/1999, (2) U.S. patent application serial no. 09/510,913, attorney docket no. 25791.7.02, filed on 2/23/2000, (3) U.S. patent application serial no. 09/502,350, attorney docket no. 25791.8.02, filed on 2/10/2000, (4) U.S. patent application serial no. 09/440,338, attorney docket no. 25791.9.02, filed on 11/15/1999, (5) U.S. patent application serial no. 09/523,460, attorney docket no. 25791.11.02, filed on 3/10/2000, (6) U.S. patent application serial no. 09/512,895, attorney docket no. 25791.12.02, filed on 2/24/2000, (7) U.S. patent application serial no. 09/511,941, attorney docket no. 25791.16.02, filed on 2/24/2000, (8) U.S. patent application serial no. 09/588,946, attorney docket no. 25791.17.02, filed on 6/7/2000, (9) U.S. patent application serial no. 09/559,122, attorney docket no. 25791.23.02, filed on 4/26/2000, (10) PCT patent application serial no.

PCT/US00/18635, attorney docket no. 25791.25.02, filed on 7/9/2000, (11) U.S. provisional patent application serial no. 60/162,671, attorney docket no. 25791.27, filed on 11/1/1999, (12) U.S. provisional patent application serial no. 60/154,047, attorney docket no. 25791.29, filed on 9/16/1999, (13) U.S. provisional patent application serial no. 60/159,082, attorney docket no. 25791.34, filed on 10/12/1999, (14) U.S. provisional patent application serial no. 60/159,039, attorney docket no. 25791.36, filed on 10/12/1999, (15) U.S. provisional patent application serial no. 60/159,033, attorney docket no. 25791.37, filed on 10/12/1999, (16) U.S. provisional patent application serial no. 60/212,359, attorney docket no. 25791.38, filed on 6/19/2000, (17) U.S. provisional patent application serial no. 60/165,228, attorney docket no. 25791.39, filed on 11/12/1999, (18) U.S. provisional patent application serial no. 60/221,443, attorney docket no. 25791.45, filed on 7/28/2000, (19) U.S. provisional patent application serial no. 60/221,645, attorney docket no. 25791.46, filed on 7/28/2000, (20) U.S. provisional patent application serial no. 60/233,638, attorney docket no. 25791.47, filed on 9/18/2000, (21) U.S. provisional patent application serial no. 60/237,334, attorney docket no. 25791.48, filed on 10/2/2000, (22) U.S. provisional patent application serial no. 60/270,007, attorney docket no. 25791.50, filed on 2/20/2001; (23) U.S. provisional patent application serial no. 60/262,434, attorney docket no. 25791.51, filed on 1/17/2001; (24) U.S. provisional patent application serial no. 60/259,486, attorney docket no. 25791.52, filed on 1/3/2001; (25) U.S. provisional patent application serial no. 60/303,740, attorney docket no. 25791.61, filed on 7/6/2001; (26) U.S. provisional patent application serial no. 60/313,453, attorney docket no. 25791.59, filed on 8/20/2001; (27) U.S. provisional patent application serial no. 60/317,985, attorney docket no. 25791.67, filed on 9/6/2001; (28) U.S. provisional patent application serial no. 60/318,386, attorney docket no. 25791.67.02, filed on 9/10/2001; and (29) U.S. utility patent application serial no. 09/969,922, attorney docket no. 25791.69, filed on 10/3/2001. In this manner, the perforated tubular member 905 modifies the flow characteristics of the perforated tubular member 145 thereby permitting the operator of the apparatus 130 to modify the overall flow characteristics of the apparatus.

As illustrated in Fig. 14, a one-way valve 1405 such as, for example, a check valve fluidly couples the interior of a pair of adjacent perforated tubular members, 145a and 145b, that extract hydrocarbons from corresponding subterranean zones A and B. In this manner, if zone B becomes depleted, hydrocarbons that are being extracted from zone A will not flow into the depleted zone B.

As illustrated in Fig. 15, the apparatus 130 is used to extract geothermal energy from a targeted subterranean geothermal zone 1505. In this manner, the operational efficiency of the extraction of geothermal energy is significantly enhanced due to the increased internal diameters of the various radially expanded elements of the apparatus 130 that permit greater volumetric flows.

The perforated tubular members, 145, 210, 212, 216, 218, and 1305 of the apparatus 130 may be cleaned by further radial expansion of the perforated tubular members. The amount of further radial expansion required to clean the radial passages of the perforated tubular members 145, 210, 212, 216, 218, and 1305 of the apparatus 130 ranged from about 1% to 2%.

Although illustrative embodiments of the invention have been shown and described, a wide range of modification, changes and substitution is contemplated in the foregoing disclosure. Accordingly, it is appropriate that the appended claims be construed broadly.




## **CLAIMS**

1. An apparatus, comprising:
  - a zonal isolation assembly positioned within a wellbore comprising:
    - 5 one or more solid tubular members, each solid tubular member including one or more external seals;
    - one or more perforated tubular members each including radial passages coupled to the solid tubular members; and
    - one or more perforated tubular liners each including one or more radial passages
    - 10 coupled to the interior surfaces of one or more of the perforated tubular members; and
    - a shoe coupled to the zonal isolation assembly;
    - wherein the perforated tubular members are formed by positioning the perforated tubular members within the wellbore and then radially expanding the perforated tubular members within the wellbore; and
    - 15 wherein the perforated tubular liners are formed by a radial expansion process performed within the wellbore.
2. A method of isolating a first subterranean zone from a second subterranean zone in a wellbore, comprising:
  - 20 positioning one or more solid tubulars within the wellbore, the solid tubulars traversing the first subterranean zone;
  - positioning one or more perforated tubulars each including one or more radial passages within the wellbore, the perforated tubulars traversing the second subterranean zone;
  - 25 radially expanding the perforated tubulars within the wellbore;
  - fluidically coupling the perforated tubulars and the solid tubulars;
  - preventing the passage of fluids from the first subterranean zone to the second subterranean zone within the wellbore external to the solid tubulars and perforated tubulars;
  - 30 positioning one or more perforated tubular liners within the interior of one or more of the perforated tubulars; and
  - radially expanding and plastically deforming the perforated tubular liners within the interior of one or more of the perforated tubulars.






3. A method of extracting materials from a producing subterranean zone in a wellbore, at least a portion of the wellbore including a casing, comprising;  
positioning one or more solid tubulars within the wellbore;  
positioning one or more perforated tubulars each including one or more radial  
5 passages within the wellbore, the perforated tubulars traversing the producing subterranean zone;  
radially expanding the perforated tubulars within the wellbore;  
fluidicly coupling the solid tubulars with the casing;  
fluidicly coupling the perforated tubulars with the solid tubulars;  
10 fluidicly isolating the producing subterranean zone from at least one other subterranean zone within the wellbore;  
fluidicly coupling at least one of the perforated tubulars with the producing subterranean zone;  
positioning one or more perforated tubular liners within the interior of one or more  
15 of the perforated tubulars; and  
radially expanding and plastically deforming the perforated tubular liners within the interior of one or more of the perforated tubulars.
4. A system for isolating a first subterranean zone from a second subterranean  
20 zone in a wellbore, comprising:  
means for positioning one or more solid tubulars within the wellbore, the solid tubulars traversing the first subterranean zone;  
means for positioning one or more perforated tubulars each including one or  
more radial passages within the wellbore, the perforated tubulars traversing the second  
25 subterranean zone;  
means for radially expanding the perforated tubulars within the wellbore;  
means for fluidicly coupling the perforated tubulars and the solid tubulars;  
means for preventing the passage of fluids from the first subterranean zone to  
the second subterranean zone within the wellbore external to the solid tubulars and  
30 perforated tubulars;  
means for positioning one or more perforated tubular liners within the interior of one or more of the perforated tubulars; and  
means for radially expanding and plastically deforming the perforated tubular liners within the interior of one or more of the perforated tubulars.



5. A system for extracting materials from a producing subterranean zone in a wellbore, at least a portion of the wellbore including a casing, comprising:
  - means for positioning one or more solid tubulars within the wellbore;
  - 5 means for positioning one or more perforated tubulars each including one or more radial passages within the wellbore, the perforated tubulars traversing the producing subterranean zone;
  - means for radially expanding the perforated tubulars within the wellbore;
  - means for fluidicly coupling the solid tubulars with the casing;
  - 10 means for fluidicly coupling the perforated tubulars with the solid tubulars;
  - means for fluidicly isolating the producing subterranean zone from at least one other subterranean zone within the wellbore;
  - means for fluidicly coupling at least one of the perforated tubulars with the producing subterranean zone;
  - 15 means for positioning one or more perforated tubular liners within the interior of one or more of the perforated tubulars; and
  - means for radially expanding and plastically deforming the perforated tubular liners within the interior of one or more of the perforated tubulars.
  
- 20 6. An apparatus for extracting geothermal energy from a subterranean formation containing a source of geothermal energy, comprising:
  - a zonal isolation assembly positioned within the subterranean formation, comprising:
    - one or more solid tubular members, each solid tubular member including one or
    - 25 more external seals;
    - one or more perforated tubular members each including radial passages coupled to the solid tubular members; and
    - one or more perforated tubular liners each including one or more radial passages coupled to the interior surfaces of one or more of the perforated tubular members; and
    - 30 a shoe coupled to the zonal isolation assembly;
    - wherein the perforated tubular members and the tubular liners are formed by a radial expansion process performed within a wellbore.

7. A method of isolating a first subterranean zone from a second subterranean zone including a source of geothermal energy in a wellbore, comprising:
- positioning one or more solid tubulars within the wellbore, the solid tubulars traversing the first subterranean zone;
  - 5 positioning one or more perforated tubulars each including one or more radial passages within the wellbore, the perforated tubulars traversing the second subterranean zone;
  - radially expanding the perforated tubulars within the wellbore;
  - fluidically coupling the perforated tubulars and the solid tubulars;
  - 10 preventing the passage of fluids from the first subterranean zone to the second subterranean zone within the wellbore external to the solid tubulars and perforated tubulars; and
  - positioning one or more perforated tubular liners within the interior of one or more of the perforated tubulars; and
  - 15 radially expanding and plastically deforming the perforated tubular liners within the interior of one or more of the perforated tubulars.
8. The apparatus of any one of claims 1 and 6, wherein a plurality of perforated tubular liners are coupled to the interior surfaces of one or more of the perforated tubular members.
- 20
9. The method of any one of claims 2, 3, and 7, wherein a plurality of perforated tubular liners are radially expanded into engagement with the interior surfaces of one or more of the perforated tubulars.
- 25
10. The system of any one of claims 4 and 5, wherein a plurality of perforated tubular liners are radially expanded into engagement with the interior surfaces of one or more of the perforated tubulars.



**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☒ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**